

Electric fixed cone valve



seleccionar	Consulta	DN(mm)	Presión de diseño (Mpa)	Caudal máximo (m ³ /s)	Carrera máxima (mm)	Carrera de inspección (mm)	Modo de operación	Tamaño del cuerpo (mm)
450	0.6-2.5	256	250	400	Turbine ,electric, pneumatic, hydraulic	650x482x482		
600	0.6-2.5	7.84	360	460	Electric, pneumatic, hydraulic	970x700x700		
800	0.6-1.6	13.50	400	480	Electric, pneumatic, hydraulic	1900x1000x1000		
100	0.6-1.6	21	400	700	Electric, pneumatic, hydraulic	1540x1200x1200		
1200	0.6-1.6	30.30	580	810	Electric, pneumatic, hydraulic	1775x1424x1424		
1400	0.6-1.0	41.20	700	830	Electric, pneumatic, hydraulic	1940x1620x1620		
1600	0.6-1.0	53.80	740	930	Electric, pneumatic, hydraulic	2260x1900x1900		
1800	0.6-1.0	60	900	1050	Electric, pneumatic, hydraulic	2460x2112x2122		
2000	0.6-1.0	84	1000	1150	Electric, pneumatic, hydraulic	2572x2300x2300		