


Pneumatic thin ball valve



| seleccionar | Consulta | DN (mm) | Tamaño (mm) | | | | | F | Z- φd | Opcional Actuacsrecuniserpara |
|-------------|----------|------------|-------------|-----|----|----|-------------|---------|----------|----------------------------------|
| | | | I | D | D1 | D2 | b | | | |
| 15 | 35 | 95 | 65 | 45 | 14 | 2 | 4- φ12 | GTD-52 | | |
| 20 | 38 | 105 | 75 | 55 | 14 | 2 | 4- φ12 | GTD-63 | | |
| 25 | 42 | 115 | 85 | 65 | 14 | 2 | 4- φ12 | GTD-63 | | |
| 32 | 50 | 135 | 100 | 78 | 16 | 2 | 4- φ16 | GTD-83 | | |
| 40 | 60 | 145 | 110 | 85 | 16 | 3 | 4- φ16 | GTD-83 | | |
| 50 | 70 | 160 | 125 | 100 | 16 | 3 | 4- φ16 | GTD-83 | | |
| 65 | 95 | 180 | 145 | 120 | 18 | 3 | 4/8- φ16 | GTD-110 | | |
| 80 | 118 | 195 | 160 | 135 | 20 | 3 | 8- φ16 | GTD-110 | | |
| 100 | 140 | 215 | 180 | 155 | 20 | 3 | 8- φ16 | GTD-127 | | |
| 125 | 175 | 245 | 210 | 185 | 22 | 3 | 8- φ16 | GTD-160 | | |
| 150 | 210 | 280 | 240 | 210 | 24 | 3 | 8- φ16 | GTD-190 | | |